

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, T28-1

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5364-65)

Set a basalt stone 15x14x5 ins., 10" in ground for cor. of secs. 3, 4, 33 and 34, marked with 3 notches on E. and W. edges; from which

- A Fir 24" dia., bears N.72°E., 21 lks. dist. mkd. T28S R1W S34 BT.
- A Fir 8" dia., bears S.40°E., 58 lks. dist. mkd. T29S R1W S3 BT.
- A Laurel 8" dia., bears S.40°W., 13 lks. dist. mkd. T29S R1W S4 BT.
- A Chingaupin 8" dia., bears S.40°W., 13 lks. dist. mkd. T28S R1W S33 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6149-50)

Intersect the old cor. of secs. 3, 4, 33 and 34, which is a basalt stone 5x14x5 ins. above ground, firmly set, marked with 3 notches on E. and W. edges, and witnessed as described by the surveyor general, except the NW. bearing tree is dead. I change this cor. to refer to secs. 33 and 34 only, obliterate marks on the old SE. and SW. bearing trees and mark a new bearing trees as follows:

- A Fir 26" dia., bears N.72°E., 21 lks. dist. mkd. T28S R1W S34 BT. (Old BT)
- A Chingaupin 9" dia., bears N.64°W., 35 lks. dist. mkd. T28S R1W S33 BT. (New BT)