

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 439100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 3 only, T30-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6068)

Set a basalt stone 12x10x8 ins., 8" in the ground for ¼ sec.cor. marked ¼ on N. face, from which
A Yellow Pine 9" dia., bears N.30°W., 85 lks. dist. mkd. ¼ S34 BT.
A Yellow Pine 10" dia., bears S.45°E., 87 lks. dist. mkd. ¼ S3 BT.

GLO Resurvey by Ernest P. Rands, Deputy Surveyor, Under contract #790, dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6102)

Intersect the ¼ sec. cor. which is a stone, 6"x5"x5" above ground, firmly set, marked and witnessed as described by the Surveyor General.

Douglas Co. Surveyors Office - John M. Powell, and crew - Feb. 20, 1968 - C.S. File 54/59-73

Found - Stone, out of place, mkd. "¼".
10" now 28" S.Pine, S.45°E., 57.4 ft., shows good scar.
9" now 25" S.Pine, N.30°W., 56.1 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office
T29S
T30S R1W ¼ S 3
1968

New BT - 15" S.Pine S.5°W., 19.6 ft. mkd. ¼ S3 CS BT.
This corner lies West of ¼ sec. cor. 34 only, T29S R1W, 33.0 ft.