

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6125)

Set a basalt stone 18x12x5", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 26" dia., bears N.11°E., 54 lks., mkd: ¼ S27 BT.
A fir, 20" dia., bears S.47°E., 58 lks., mkd: ¼ S34 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - May 29, 1969 - C.S. File 54/82-69

Found - 26" D.Fir, now 38" N.11°E., 32.6 (Rec. 35.6 slope) shows good scar.
20" D.Fir, now 30" S.47°W., (Rec. S.47°E.) 38.3.
Opened for scribe "4"
No trace of cor. stone.

Set - Brass cap at ¼ cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 ¼ S 27
S 34

BTs OK and tagged.