

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6127)

Set a basalt stone 12x8x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 8" dia., bears N.14°E., 10 lks., mkd: ¼ S15 BT.
A fir, 20" dia., bears S.45°E., 76 lks., mkd: ¼ S22 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April 1969 - C.S. File 54/82-7

Found - 18x10x6 stone, firmly set at corner, mkd: "¼" on north face.
20" D.Fir now stump, S.45°E., 50.2 ft. shows good scar.
8" D.Fir now stump, N.14°E., 6.6 ft. opened for scribing, rotten face but fd definite scribe marks.

Set brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE ¼ S 15
1969 S 22

New BTs- 7" D.Fir N.44°E., 25.2 ft. mkd: "¼ S15 CS BT"
19" Laurel S.48°W., 38.8 ft. mkd: "¼ S22 CS BT"