

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 442500

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 10 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6128)

-----

~~A fir, 6" dia., for ¼ sec. cor. I mark ¼ on S10 on N side & 15 on S side, from which  
A pine, 8" dia., bears N.76°E., 40 lks., mkd: ¼ S10 BT.  
A fir, 8" dia., bears S.66°E., 25 lks., mkd: ¼ S15 BT.~~

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6164)

-----

Intersect the old ¼ sec. cor., which is a fir, 10" dia., marked & witnessed as described by the surveyor general. **I change this cor. to refer to sec. 15**, only, obliterate marks on the NE, BT & on the N side of the cor. tree, & remark cor., ¼ S15 on S side

**East 1.89 chs. along the N bdy of sec. 15**

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 10 only, with brass cap marked

¼ S 10  
1922

from which

A fir, 8" dia., bears N.20°E., 19 lks., mkd: ¼ S10 BT.

A maple, 4" dia., bears N.88°W., 13 lks., mkd: ¼ S10 BT.