

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. cor. for 34 & 35 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Resurvey by Ernest P. Rands, Deputy Surveyor, Under contract #790, dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6103)

Set a basalt stone 24x8x8 ins., 18" in the ground for cor. of secs. 34 and 35, marked with 2 notches on E. and 4 notches on W. edge, from which
A W.Fir 28" dia., bears N.58°E., 19 lks. dist. mkd. T29S R1W S35 BT.
A Red Fir 48" dia., bears N.59½°W., 86 lks. dist. mkd. T29S R1W S34 BT.

Dennis Gaylord, U.S.F.S. (Deputized by the DCSO) Wit: Randal Lopez - Nov. 17, 1977 - C.S. File 59/42-15

Found - Stone 8"x8"x10" above ground surface. Stone is solidly set and mkd. with 2 notches on E. edge and 4 notches on the W. edge.
A 2½" alum. cap on a 3/4" I.Rod is set so the cap is over the SW. edge of the corner stone. The cap, not of record, is stamped "1967 U.S.P.C. Prop. Cor. RE 4287 34 35 3 R1W Do Not Disturb".
The orig. 48" now 53" D.Fir bears N.59½°W., 56.8 ft. Has a healed scar. This tree is almost dead. Orig. BT to the NE. is down and well decayed. Stump hole bears N.58°E., 12.54 ft.
Bearing trees not of record, as follows:
A 14" D.Fir bears N.1½°W., 14.5 ft. Has a single healed blaze.
A 23" W.Fir bears N.49°E., 30.7 ft. Some scribing visible on a nearly healed blaze.
A 6" D.Fir bears S.29½°W., 7.0 ft. scribing visible on a single blaze "S3 BT T30S R1W."
I placed BT signs on all accessories.