

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6116)

-----  
Set a basalt stone 24x10x4", 18" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which  
A W.Fir, 18" dia., bears N.6°E., 30 lks., mkd: ¼ S35 BT.  
A R.Fir, 48" dia., bears S.76°W., 77 lks., mkd: ¼ S34 BT.

-----  
Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - May 12, 1969 - C.S. File 54/82-54

-----  
Found - 18" W.Fir now down & cut, N.6°E., 19.8 stump lying on face.  
48" D.Fir now stump, S.76°W., 50.8 opened stump for scribing "¼"  
No trace of cor. stone due to logging in area.  
Set - Brass cap at ¼ cor. mkd: COUNTY SURVEYORS T29S R1W  
OFFICE 1969 ¼  
S 34|S 35  
New BTs- 10" Hemlock N.58°W., 9.4 scribed ¼ S34 CS BT.  
15" R.Fir N.59°E., 36.3 scribed ¼ S35 CS BT.