

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6116)

Set a basalt stone 16x14x6", 11" in the ground for cor. of secs. 26, 27, 34, & 35 mkd with 1 notch on S & 2 notches on E edge, from which
A sugar pine, 36" dia., bears N.76°E., 60 lks., mkd: T29S R1W S26 BT.
A fir, 16" dia. bears S.17°E., 30 lks mkd: T29S R1W S35 BT
A fir, 16" dia. bears S.69°W., 14 lks mkd: T29S R1W S34 BT
A fir, 30" dia., bears N.62°W., 124 lks., mkd: T29S R1W S27 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - May 29, 1969 - C.S. File 54/82-70

Found - 36" S.Pine, now 46" N.76°E., 39.6 shows scar.
16" D.Fir, now 18" S.17°E., 19.8 shows scar.
16" D.Fir, now 16" S.69°W., 9.2 shows good scar.
30" D.Fir now 39" N.62°W., 81.8 shows good scar.
Also - 16x14x6 stone firmly set at sec. cor. mkd. 2 notches East 1 notch south.
Set brass cap at sec. cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 S 27 | S 26
S 35 | S 34

All BTs ok & tagged.