

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6117-8)

-----  
Set a basalt stone 20x9x8", 15" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which  
A fir, 30" dia., bears N.63°E., 94 lks., mkd: 1/4 S26 BT.  
A fir, 12" dia., bears N.59°W., 45 lks., mkd: 1/4 S27 BT.

-----  
Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - June 2, 1969 - C.S. File 54/82-76

-----  
Found - 30" D.Fir, now 37" N.63°E., 59.2 (Rec. 62.0)  
12" R.Fir, now 23" N.59°W., 27.7 (Rec. 29.7) shows good scar.  
Orig. dist. probably sloped  
20x9x8 stone, firmly set, at 1/4 cor. mkd. 1/4 on West face.

Set - Brass cap at 1/4 cor. mkd: COUNTY SURVEYORS T29S R1W  
OFFICE 1969 S 27|S 26  
1/4

BTs OK & tagged.