

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6118)

-----  
Set a basalt stone 22x10x6", 17" in the ground for cor. of secs. 22, 23, 26, & 27 mkd with 2 notches on S & E edges, from which  
A fir, 40" dia., bears N.22°E., 59 lks., mkd: T29S R1W S23 BT.  
A fir, 30" dia., bears S.5°E., 75 lks., mkd: T29S R1W S26 BT.  
A fir, 24" dia., bears S.47°W., 47 lks., mkd: T29S R1W S27 BT.  
A fir, 16" dia., bears N.37½°W., 59 lks., mkd: T29S R1W S22 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - June 10, 1969 - C.S. File 54/82-84

-----  
Found - 40" D.Fir now 45", N.16°E., (Rec. N.22°E.) 38.9 shows good scar.  
30" D.Fir now S.10°E., (Rec. S.5°E.) 49.5 shows good scar.  
24" D.Fir now 27" S.44°W., (Rec. S.47°W.) 31.0 shows good scar.  
16" R.Fir now 20" N.43°W., (Rec. N.37½°W. 38.9) shows good scar. Parts of scribe "S2" visible.  
22x10x6 stone firmly set at sec. cor. mkd. 2 notches on the South & East sides.

Set - Brass cap at sec. cor. mkd. COUNTY SURVEYORS T29S R1W  
OFFICE 1969 S 22 | S 23  
S 27 | S 26

All BTs ok & tagged.