

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6120-1)

Set a basalt stone 18x12x10", 12" in the ground for cor. of secs. 14, 15, 22, & 23 mkd with 3 notches on S & 2 notches on E edge, from which
A fir, 48" dia. bears N.22°E., 44 lks mkd: T29S R1W S14 BT
A laurel, 10" dia., bears S.40°E., 65 lks., mkd: T29S R1W S23 BT.
A fir, 40" dia. bears S.54°W., 49 lks mkd: T29S R1W S22 BT
A fir, 40" dia. bears N.57°W., 33 lks mkd: T29S R1W S15 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - June 3, 1969 - C.S. File 54/82-79

Found - 40" D.Fir now 46" N.57°W., 21.8 shows good scar.
48" D.Fir now 51" N.22°E., 29.0 shows good scar.
40" D.Fir now 47" S.54°W., 32.3 shows good scar.
No trace of SE BT (10" Laurel)
Also - Found cor. stone approx. 18x12x10 notches on E & S faces.
Set - Brass cap at sec. cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 S 15|S 14
S 22|S 23