

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6122)

Set a basalt stone 14x8x6", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which

A fir, 14" dia., bears N.52°E., 8 lks., mkd: 1/4 S14 BT.

A fir, 14" dia., bears S.38°W., 23 lks., mkd: 1/4 S15 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - June 3, 1969 - C.S. File 54/82-78

Found - 14" D.Fir now dead, S.38°W., 15.2 shows good scar.
14" D.Fir now down, N.52°E., 5.3 tree rotted.

Stone 14x8x6 stone firmly set at 1/4 cor. mkd. 1/4 on West face.

Set Brass cap at 1/4 cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969

1/4
S 15 | S 14

New BTs- 17" D.Fir S.87 1/2°W., 29.2 scribed 1/4 CS BT.

18" D.Fir N.84°E., 34.2 scribed 1/4 CS BT.

Scribing done with axe.