

PRIMARY CORNER DESCRIPTION Cor. Secs. 14 & 15 (North) only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6123)

Set a basalt stone 15x7x5", 10" in the ground for cor. of secs. 10, 11, 14, & 15 mkd with 4 notches on S & 2 notches on E edge, from which

- A fir, 14" dia. bears N.28°E., 18 lks mkd: T29S R1W S11 BT
- A cedar, 10" dia bears S.82°E. 32 lks mkd: T29S R1W S14 BT
- A fir, 10" dia. bears S.13°W., 13 lks mkd: T29S R1W S15 BT
- A fir, 14" dia. bears N.38°W., 21 lks mkd: T29S R1W S10 BT

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6165)

Intersect the old cor. of secs. 10, 11, 14 & 15, which is a basalt stone, 5x7x5", above ground, firmly set, marked with 4 notches on S & 2 notches on E edges, witnessed as described by the surveyor general. I obliterate marks on the NE & NW bearing trees, and change this cor. to refer to secs. 14 & 15 only, & mark 4 notches on W edge of cor. from which

- A cedar, 12" dia., bears S.82°E., 32 lks., marked T29S R1W S14 BT. (Old BT)
- A fir, 14" dia., bears S.13°W., 13 lks., mkd T29S R1W S15 BT. (Old BT.)

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - May 27, 1969 - C.S. File 54/82-73

Found - 12" cedar, now 14" S.82°E., 21.1' scribe visible S R 1 W
 14" D.Fir now 8" & dead, S.13°W., 8.6' open for scribe "T29S R"
 Orig. BTs for sec. 10 & 11 tagged by Forest Service, however, scribing destroyed in 1922.
 15x7x5 stone, firmly set at sec. cor. mkd. 4 notches & 2 notches.

Set Brass cap at sec. cor. mkd: COUNTY SURVEYORS T29S R1W
 OFFICE 1969 S 10
 S 15 | S 14

New BT - 12" D.Fir S.46°W., 22.5', scribed T29S R1W S15 CS BT
 Note - This cor. lies 122.1' west of sec. cor. 10|11
 14