

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6117)

-----  
Set a basalt stone 15x10x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A cedar, 16" dia., bears S.12°W., 45 lks., mkd: ¼ S35 BT.  
A fir, 16" dia., bears N.31¾°W., 47 lks., mkd: ¼ S26 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - May 12, 1969 - C.S. File 54/82-55

-----  
Found - 16" Cedar, now 18" S.12°W., 29.7 scribe visible S35  
16" Fir, now stump, N.31¾°W., 31.0 scribe visible  
"26" BT.

Fd. stone approx. size, no marks, at cor.  
Set - Brass cap at ¼ cor. mkd: COUNTY SURVEYORS T29S R1W  
OFFICE 1969 ¼  
S 26  
S 35

New BT - 11" R.Fir N.76°W., 32.4 scribed ¼ S26 CS BT.  
SW BT Ok & tagged.