

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. SEcs. 23 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6119)

Set a basalt stone 15x10x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A pine, 18" dia., bears S.12°W., 25 lks., mkd: ¼ S26 BT.
A fir, 20" dia., bears N.5°W., 25 lks., mkd: ¼ S23 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - June 10, 1969 - C.S. File 54/82-85

Found - 20" D.Fir now down, N.5°W., 16.5. Tree lying on face, scribing found "3" "B". No trace of SW BT or cor. stone.

Set - Brass cap at ¼ cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 ¼ S 23
S 26

New BTs- 14" Hemlock S.35°E., 34.9 scribed ¼ S26 CS BT.
7" Cedar N.30°W., 33.3 scribed ¼ S23 CS BT.