

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6121)

A fir, 30" dia., for 1/4 sec. cor., marked 1/4 S14 on N side & 23 on S side; from which

A cedar, 20" dia., bears S.29°E., 56 lks., mkd: 1/4 S23 BT.

A fir, 36" dia., bears N.40°W., 24 lks., mkd: 1/4 S14 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April 1969 - C.S. File 54/82-9

Found - 30" now 38" corner tree, good scars on North & South face.

20" now 28" cedar, S.29°E., 37.0 ft shows good scar.

36" now 41" D.Fir N.40°W., 15.8 ft. tree opened before pitched over, scribe visible.

Set - Brass cap on East side of corner tree mkd: T29S R1W

COUNTY SURVEYORS

OFFICE 1969

1/4 S 14
S 23

All BTs ok & tagged.