

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 14 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6123-4)

Set a basalt stone 15x12x7", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 20" dia., bears S.68½°W., 65 lks., mkd: ¼ S14 BT.
A hemlock, 15" dia., bears N.68½°W., 65 lks. mkd: ¼ S11 BT

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6166)

Intersect the old ¼ sec. cor. which is a basalt stone, 15x12x7" firmly set, marked & witnessed as described by the surveyor general. I obliterate marks on the NW BT, change this cor. to refer to sec. 14 only, & reset the stone, 10" in the ground, marked ¼ S14 on S face, from which
A chinquapin, 8" dia., bears S.5°E., 28 lks., mkd: ¼ S14 BT. (New BT)
A fir, 20" dia., bears S.68½°W., 65 lks., mkd: ¼ S14 BT. (Old BT)