

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 542500

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 11 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6123-4)

-----  
Set a basalt stone 15x12x7", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A fir, 20" dia., bears S.68½°W., 65 lks., mkd: ¼ S14 BT.  
A hemlock, 15" dia., bears N.68½°W., 65 lks. mkd: ¼ S11 BT

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6166)

-----  
Intersect the old ¼ sec. cor. which is a basalt stone, 15x12x7" firmly set, marked & witnessed as described by the surveyor general. I obliterate marks on the NW BT, change this cor. to refer to sec. 14 only, & reset the stone, 10" in the ground, marked ¼ S14 on S face  
**S.89°50'E., 2.32 chs. along the N. Bdy. of Sec. 14**  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor., with brass cap marked ¼ S 11  
1922  
from which  
A hemlock, 9" dia., bears N.44°E., 43 lks., mkd: ¼ S11 BT.  
A hemlock, 10" dia., bears N.49°W., 14 lks., mkd: ¼ S11 BT