

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 572700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only, T28-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5363-64)

Set a basalt stone 12x10x6 ins., 8" in the ground for ¼ sec. cor. marked ¼ on N. face; from which
A Pine 12" dia., bears N.26°E., 67 lks. dist. mkd. ¼ S35 BT.
A Fir 10" dia., bears S.43°E., 30 lks. dist. mkd. ¼ S2 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6152)

Intersect the old ¼ sec. cor., which is a basalt stone, 4x10x6 ins. above ground, firmly set, marked ¼ on N. face, and witnessed as described by the surveyor general, except the NE. bearing tree is dead. I obliterate marks on the old SE. bearing tree, change this cor. to refer to sec. 35 only, and mark new bearing trees as follows:
A Fir 6" dia., bears N.24°E., 21 lks. dist. mkd. ¼ S35 BT.
A Fir 10" dia., bears N.10°W., 59 lks. dist. mkd. ¼ S35 BT