

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Resurvey by Ernest P. Rands, Deputy Surveyor, Under contract #790, dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6105)

A Sugar Pine 24" dia., for cor. of secs. 35 and 36, I mark T29S S 36 on NE. and R1W S35 on NW. side, with 1 notch on E. and 5 notches on W. side, from which
 A Sugar Pine 24" dia., bears N.35°E., 8 lks. dist. mkd. T29S R1W S36 BT.
 A Fir 16" dia., bears N.53°W., 52 lks. dist. mkd. T29S R1W S35 BT.

Thomas E. Shrum, Jr. - For: U.S. Plywood - June 1967 - C.S. File 55/106 and M 36-14

Found - Sugar Pine stump, Corner.
 26" Sugar Pine, N.35°E., 5.30 ft., down.
 16" Fir, N.53°W., 34.5 ft.
Set 2½" alum. cap, from which
 24" Fir N.45°E., 13.70 ft.

Loyd R. Moffit - For: U.S. Forest Service - Dec. 1985 - C.S. File 62/30-33

Found - 3/4" Iron pipe with 2½" alum. cap exposed 14".
 Corner was re-monumented in 1967 by RE #4287.
New BT - Marked a 10" Cedar BT which bears N.50°W., 71.9 ft. from the corner, scribed "T29S R1W S35 BT"