

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6107)

Set a basalt stone 18x10x6", 12" in the ground for cor. of secs. 25, 26, 35, & 36 mkd with 1 notch on S & E edges, from which
A fir, 24" dia. bears N.65°E., 58 lks mkd: T29S R1W S25 BT
A fir, 24" dia. bears S.80°E., 26 lks mkd: T29S R1W S36 BT
A fir, 24" dia. bears S.71°W., 42 lks mkd: T29S R1W S35 BT
A fir, 30" dia. bears N.74°W., 29 lks mkd: T29S R1W S26 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - May 9, 1969 - C.S. File 54/82-53

Found - 24" D.Fir now stump, S.80°E., 17.1 scribe visible T29S R1W.
24" D.Fir now stump, N.65°E., 38.8 shows good scar.
24" D.Fir now stump, S.71°W., 27.7 shows good scar.
30" D.Fir now down N.74°W., 19.1 shows good scar.
Stone approx. size at cor.
Set - Brass cap at sec. cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 S 26 | S 25
S 35 | S 36
New BTs- 10" Cedar N.18°E., 35.3 scribed T29S R1W S25 CS BT.
14" Cedar N.23°W., 27.2 scribed T29S R1W S26 CS BT.
25" D.Fir S.77°W., 46.0 scribed T29S R1W S35 CS BT.
19" Cedar S.88°E., 96.3 scribed T29S R1W S36 CS BT.