

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6109)

Set a basalt stone 15x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A fir, 40" dia., bears N.80°E., 48 lks., mkd: ¼ S25 BT.

A fir, 20" dia., bears S.62°W., 61 lks., mkd: ¼ S26 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - May 22, 1969 - C.S. File 54/82-67

Found - 40" D.Fir now 44" N.80°E., 31.7' Shows good scar.

20" D Fir now 25" S.62°W., 40.3' Shows good scar.

Also 15x8x6 Stone at ¼ cor. Mkd. on West Face

Set - Brass cap at ¼ cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 ¼ S 26|S 25

BTs are OK & tagged.

Note - This cor. lies directly under large down D.Fir. This tree was line tree at 39.75 chains going North.