

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6109)

-----  
Set a basalt stone 18x14x10", 12" in the ground for cor. of secs. 23, 24, 25, & 26 mkd with 2 notches on S & 1 notch on E edge, from which  
A fir, 30" dia., bears N.82°E., 37 lks., mkd: T29S R1W S24 BT.  
A chinquapin, 14" dia., bears S.18½°E., 37 lks., mkd: T29S R1W S25 BT.  
A W.Fir, 20" dia., bears S.64°W., 10 lks., mkd: T29S R1W S26 BT.  
A R.Fir, 48" dia., bears N.23°W., 29 lks., mkd: T29S R1W S23 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April 23, 1969 - C.S. File 54/82-26

-----  
Found - 18x14x19 Stone, firmly set & chipped, no marks.  
40", now 55" D.Fir, N.23°W, 19.1 ft. shows good scar  
20", now 19" W.Fir, S.64°W., 6.6 ft., rotten face found, definite scribe marks.  
30", now 37" D.Fir, N.82°E. 18.5 ft. (Record 24.4'), shows good scar.  
No trace of SE BT.  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T29S R1W  
OFFICE S 23 | S 24  
1969 S 26 | S 25  
Reblazed & rescribed -  
29" W.Fir S.64°W., 6.6 ft. mkd: T29S R1W S26 CS BT.  
New BT - 13" R.Fir S.83°E., 86.9 ft. mkd: T29S R1W S25 CS BT.