

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6111)

Set a basalt stone 15x10x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A cedar, 30" dia., bears S.76°E., 76 lks., mkd: ¼ S24 BT.
A hemlock, 18" dia., bears S.46°W., 8 lks., mkd: ¼ S23 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - April/May 1969 - C.S. File 54/82-27

Found - 30", now 48" Cedar, S.76°E. 50.2 ft., opened for scribe.

18" Hemlock, now down & rotted, S.46°W. 5.3 ft.
15x19x8 Stone found mkd. "¼" firmly in place.

Set - Brass Cap at Cor. County Surveyors T29S R1W
Office, 1969 ¼ S 23|S 24

Reblazed & Rescribed -

48" Cedar S.76°W. 50.2 ft., mkd: ¼ S24 CS BT.

New BT - 9" Cedar N.14°W. 19.7 ft., mkd: T29S R1W S23 CS BT.

Note - This corner lies approx. 35.0' south of spring branch.