

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION W.C. Cor. Secs. 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6111-2)

The point for cor. of secs. 13, 14, 23, & 24, falls on bed rock on left bank of North Fork of South Umpqua River, course S.20°W.

Cut X on bed rock on exact cor. point, from which
A fir, 30" dia., bears N.46°E., 124 lks., mkd: T29S R1W S13 BT.
A fir, 15" dia., bears S.28°E., 70 lks., mkd: T29S R1W S24 BT.
A cedar, 18" dia., bears S.7°W., 132 lks., mkd: T29S R1W S23 BT.
A cedar, 24" dia., bears N.53°W., 195 lks., mkd: T29S R1W S14 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - June 2, 1969 - C.S. File 54/82-77

Found - 15" D.Fir, now 19" S.28°E., 46.2 Shows good scar
18" Cedar now 23" S.7°W., 87.1 Scribe visible T29S R1W S23
24" Cedar now 39" N.53°W., 128.7 Scribe visible S14

Did not measure in this tree across river.
No trace tree of NE BT.

Note - This Cor. falls in So. Umpqua River
Set - Brass Cap for Wit. Cor. mkd: T29S R1W
COUNTY SURVEYORS WC 55'
OFFICE 1969 WEST TO
S 14 | S 13
S 23 | S 24

New BTs- 24" D.Fir N.18°W., 5.0 scribed WC T29S R1W S13 CS BT
34" D.Fir S.10°W., 6.0 scribed WC T29S R1W S24 CS BT

Note - This wit. cor. lies on high east bank of South Umpqua River.