

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6113-4)

Set a basalt stone 14x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 10" dia., bears N.43°E., 22 lks., mkd: ¼ S13 BT.
A fir, 12" dia., bears S.50°W., 17 lks., mkd: ¼ S14 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - May 22, 1969 - C.S. File 54/82-68

Found - 14x8x6 corner stone in place mkd. ¼ West face & two good BTs.
10" D.Fir now 11", N.43°E., 14.5 ft shows good face.
12" D.Fir now 15", S.50°W., 11.2 ft. shows good face

Set - Brass cap at ¼ cor. from bearing & dist. from both BTs mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 ¼ S 14|S 13

Note - No new bearing objects needed. This cor. lies on steep east slope & a rock bluff bearing east 25'.