

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 603100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2 only, T30-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 14 Page(s) 6060)

Set post cor. secs. 35, 36, 1 and 2, from which
A Hemlock 6" dia., bears S.30°E., 6 lks. dist.
A Hemlock 30" dia., bears S.40°W., 17 lks. dist.
A Hemlock 4" dia., bears N.37°E., 26 lks. dist.
A Hemlock 9" dia., bears N.50°W., 45 lks. dist.

GLO Resurvey by Ernest P. Rands, Deputy Surveyor, Under contract #790, dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6105)

Intersect the cor. of secs. 1 & 2, T30S R1W which is an old post marked and witnessed as described by the Surveyor General. I destroy the old post and in its place, Set a basalt stone 15x10x6 ins., 10" in the ground for cor. of secs. 1 & 2, marked with 1 notch on E. edge and 5 notches on W. edge.

Thomas E. Shrum, Jr. - For: U.S. Plywood - June 1967 - C.S. File 55/106 - M 36-14

Found - Brass cap and 30" Hemlock, S.40°W., 11.2 ft.
New BTs- 32" Fir S.46°E., 20.9 ft.
28" Fir S.60°W., 17.50 ft.
34" Fir N.41°30'E., 45.80 ft.

Lloyd R. Moffit, LS #944 - For: U.S. Forest Service - May 1985 - C.S. File 63/8-15

Found - 2½" alum. cap on ¾" iron pipe.
30" Fir bears S.62°W., 17.2 ft., scribe visible.
48" dead Fir bears N.46°E., 20.5 ft., scribe visible.
40" Fir bears N.10°E., 88.9 ft., scribe visible.
New BT - 10" Fir bears S.33°E., 24.1 ft. scribed T30S R1W S1 BT.