

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, & 12 (South) only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6114)

Set a basalt stone 15x8x7", 10" in the ground for cor. of secs. 11, 12, 13, & 14 mkd with 4 notches on S & 1 notch on E edge, from which

- A fir, 40" dia., bears N.10°E., 49 lks., mkd: T29S R1W S12 BT.
- A laurel, 14" dia., bears S.21°E., 13 lks., mkd: T29S R1W S13 BT.
- A fir, 8" dia., bears S.40°W., 35 lks., mkd: T29S R1W S14 BT.
- A fir, 18" dia., bears N.76½°W., 58 lks., mkd: T29S R1W S11 BT.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6166-7)

Intersect the cor. of secs. 11, 12, 13 & 14, which is a basalt stone, 5x8x7", above ground, firmly set, marked with 4 notches on S & 1 notch on E. edge, witnessed as described by the surveyor general. I obliterate marks on the NE & NW bearing trees, change this cor. to refer to secs. 13 & 14, & mark 5 notches on W edge of stone

N.89°58'E., 2.98 chs. along the N. Bdy. of sec. 13
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 11 & 12, with brass cap mkd

T29S	R1W
<u>S 11</u>	<u>S 12</u>
S 13	
1922	

from which

- A dogwood, 8" dia., bears N.56°E., 38 lks., mkd: T29S R1W S12 BT.
- A fir, 9" dia., bears N.7°W., 18 lks., mkd: T29S R1W S11 BT.