

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, T28-1

Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5363)

Set a basalt stone 15x12x10 ins. 10" in ground for cor. of secs. 1, 2, 35 and 36, marked with 1 notch on E. and 5 notches on W. edges; from which

- A Fir 14" dia., bears N.84°E., 60 lks. dist. mkd. T28S R1W S36 BT.
- A Cedar 30" dia., bears S.60°E., 26 lks. dist. mkd. T29S R1W S1 BT.
- A Fir 14" dia., bears S.22°W., 74 lks. dist. mkd. T29S R1W S2 BT.
- A Cedar 24" dia., bears N.81°W., 53 lks. dist. mkd. T28S R1W S35 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6153)

Intersect the old cor. of secs. 1, 2, 35 and 36, which is a basalt stone 5x12x10 ins. above ground, firmly set, marked with 1 notch on E. and 5 notches on W. edge, and witnessed as follows:

- A Fir 16" dia., bears N.84°E., 60 lks. dist. mkd. T28S R1W S36 BT.
- A Cedar 24" dia., bears N.81°W., 53 lks. dist. mkd. T28S R1W S35 BT.

I change this cor. to refer to secs. 35 and 36 only, and obliterate marks on the old SE. and SW. bearing trees.