

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Resurvey by Ernest P. Rands, Deputy Surveyor, Under contract #790, dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6106)

-----  
Set a basalt stone 18x10x6 ins., 12" in the ground for ¼ sec. cor. common to 2 quarters of sec. 36 only, ¼ on N. face, from which

A Fir 16" dia., bears N.6°E., 74 lks. dist. mkd. ¼ S36 BT  
A Pine 16" dia., bears N.28½°W., 107 lks. dist. mkd. ¼ S36 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June/July 1968 - C.S. File 54/59-105

-----  
Found - Stone, firmly set at ¼ corner mkd. "¼" on N. face. 16" now 21" D.Fir N.6°E., 48.8 ft. some scribe work visible.

16" now 30" Pine N.28½°W., 70.6 ft., shows scar.  
Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 1 W  
¼ S 36  
T30S  
1968

Bearing trees OK and tagged.

This corner lies 205.3 ft. West of ¼ cor. sec. 1, T30S R1W.