

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6108)

Set a basalt stone 24x6x4", 18" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A yew, 10" dia., bears N.65°E., 73 lks., mkd: ¼ S25 BT.
A fir, 40" dia., bears S.60°W., 70 lks., mkd: ¼ S36 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - May 9, 1969 - C.S. File 54/82-51

Found - 10" Yew now 10" N.65°E., 48.2' scribe visible ¼ S 25
Stone at ¼ cor. Mkd. ¼ on N Face
Possible large fir cut with burnt face (S.W. BT)
Set - Brass cap at ¼ Cor. Mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 ¼ S 25
S 36

New BT - 6" Hemlock N.67°E., 9.8 ft.
Scribed ¼ S 25 CS BT
5" Hemlock S.82½°E., 5.4 ft Scribed ¼S CS BT
This cor. in very old unit, very brushy, no good BTs