

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6110)

-----  
Set a basalt stone 24x7x6", 18" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A fir, 20" dia., bears S.65°E., 43 lks., mkd: ¼ S25 BT.  
A fir, 18" dia., bears N.9°W., 12 lks., mkd: ¼ S24 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - May 8, 1969 - C.S. File 54/82-50

-----  
Found - 18" D.Fir now stump, shows good scar.  
24x7x6 stone firmly set: "¼ cor. mkd. ¼ on N face.  
No trace of SE BT because of Rd.

Set - Brass cap at ¼ cor. mkd:  
COUNTY SURVEYORS OFFICE T29S R1W  
1969 ¼ S 24  
S 25

New BTs- 6" hemlock S.29°E., 10.9 scribed ¼ S 25 CS BT.  
6" hemlock N.52½°E., 12.6

Note - This cor. lies 60.0 west of rd. on top of high cut.