

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6113)

Set a basalt stone 18x6x5", 12" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which

A W.Fir, 10" dia., bears S.50°W., 6 lks., mkd: 1/4 S24 BT.

A R.Fir, 14" dia., bears N.22°W., 10 lks., mkd: 1/4 S13 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - May 19, 1969 - C.S. File 54/82-61

Found - 10" W.Fir, now 12" S.50°W., 4.0 ft. shows good scar.
14" R.Fir, now down, N.22°W., 6.6 ft.

Also 18x6x5 stone firmly set at 1/4 cor. mkd. 1/4 on North face.

Set - Brass cap at 1/4 cor. mkd: COUNTY SURVEYORS T29S R1W
OFFICE 1969 1/4 S 13
S 24

New BT - 16" D.Fir N.60°W., 24.4 ft. scribed 1/4 S13 CS BT.