

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6115)

-----

Set a basalt stone 14x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A fir, 30" dia., bears S.70°W., 84 lks., mkd: ¼ S13 BT.

A fir, 30" dia., bears N.28°W., 48 lks., mkd: ¼ S12 BT.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6167-8)

-----

Intersect the old ¼ sec. cor. which is a basalt stone, 14x8x6" firmly set, marked & witnessed as described by the surveyor general. I obliterate marks on the NW BT, & reset the stone, 10" in the ground, for ¼ sec. cor. of sec. 13 only, mkd. ¼ S13 on S face, from which

A laurel, 11" dia., bears S.89°E., 82 lks., mkd: ¼ S13 BT.  
(New BT)

A fir, 30" dia., bears S.70°W., 84 lks., mkd: ¼ S13 BT.  
(Old BT)