

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 642500

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 12 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Ernest P. Rands, Deputy Surveyor - Under Contract No. 790 dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6115)

-----

Set a basalt stone 14x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

- A fir, 30" dia., bears S.70°W., 84 lks., mkd: ¼ S13 BT.
- A fir, 30" dia., bears N.28°W., 48 lks., mkd: ¼ S12 BT.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 14 Page(s) 6167-8)

-----

Intersect the old ¼ sec. cor. which is a basalt stone, 14x8x6" firmly set, marked & witnessed as described by the surveyor general. I obliterate marks on the NW BT, & reset the stone, 10" in the ground, for ¼ sec. cor. of sec. 13 only, mkd. ¼ S13 on S face

N.89°58'E., 2.74 chs. along the N. Bdy. of sec. 13

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor., with brass cap marked ¼ S 12  
1922

from which

- A sugar pine, 48" dia. bears N.55°E., 72 lks mkd: ¼ S12 BT
- A fir, 16" dia., bears N.51°W., 90 lks., mkd: ¼ S12 BT.