

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 643100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 1 only, T30-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 14 Page(s) 6059)

-----  
Set ¼ sec. post, from which  
A Fir 12" dia., bears S.87°W., 31 lks. dist.  
A Fir 12" dia., bears N.80°W., 27 lks. dist.

GLO Resurvey by Ernest P. Rands, Deputy Surveyor, Under contract #790, dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6106)

-----  
Intersect the old ¼ sec. cor as described by the surveyor general. The old post being badly decayed, I remove same and at the same place, Set a basalt stone 15x8x6 ins., 10" in the ground marked ¼ on S. face, for ¼ sec. cor. common to 2 quarters of sec. 1 only.

Douglas Co. Surveyors Office - John M. Powell, and crew - June/July 1968 - C.S. File 54/59-106

-----  
Found - Stone, firmly set at ¼ cor. mkd. "¼" on S. face.  
12" now 32" D.Fir, N.80°W., 17.8 ft., tree badly scared.  
12" now 34" D.Fir, S.77°W., (Rec. S.87°W.) 20.5 ft., has burnt cat face.

Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S R 1 W  
-----  
¼ S 1  
T 30 S  
1968

Reblazed and rescribed:  
34" D.Fir S.77°W., 20.5 ft. mkd. ¼ S1 CS BT.  
New BT - 9" Hemlock S.64°E., 14.0 ft. mkd. ¼ S1 CS BT.  
This corner lies 205.3 ft. E. of ¼ cor. sec. 36 only, T29-1