

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 666700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only, T28-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5362-63)

Set a basalt stone 14x12x5 ins., 10" in ground for ¼ sec. cor. marked ¼ on N. face; from which
A Fir 36" dia., bears S.50°E., 55 lks. dist. mkd. ¼ S1 BT.
A Fir 36" dia., bears N.50°W., 33 lks. dist. mkd. ¼ S36 BT

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 - (DCSO records Vol. 15 Page(s) 6154)

Intersect the old ¼ sec. cor., which is a basalt stone, 4x12x5 ins., above ground, firmly set, marked ¼ on N. face, and witnessed as described by the surveyor general. I obliterate marks on the old SE. bearing tree, change this cor. to refer to sec. 36 only, and mark a bearing tree as follows:
A Chinquapin 8" dia., bears N.13°E., 65 lks. dist. mkd. ¼ S36 BT. (New BT)
A Fir 36" dia., bears N.50°W., 6 lks. dist. mkd. ¼ S36 BT. (Old BT)