

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 700137

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31 only, T29-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Contract #797, dated April 19, 1910 - (DCSO records Vol. 15 Page(s) 6134)

Set a conglomerate stone 18x12x6 ins., 12" in the ground, for cor. of secs. 30 and 31 marked with 5 notches on N. and 1 notch on S. edge, from which

A Hemlock 9" dia., bears N.44°E., 10 lks. dist. mkd. T29S R1E S30 BT.

A Hemlock 6" dia., bears S.45°E., 5 lks. dist. mkd. T29S R1E S31 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - May 15, 1969 - C.S. File 54/82-58

Looked for, Not found. ¼ cor. sec. 36, T29S R1W and this cor. which lie approx. 3 chains apart, fall in edge of road and also large shale pit. Found forest location tag approx. 12 chains S. and location tag 10 chains E. of corners. I ran line N. and W. chaining E-W line with no results.