

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 700177

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only, T29-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 15 Page(s) 6135)

-----  
Set a basalt stone 18x10x4 ins., 12" in the ground for ¼ sec. cor. on W. bdy. sec. 30, marked ¼ on E. face, from which  
A Fir 8" dia., bears N.18°E., 106 lks. dist. mkd. ¼ S30 BT  
A Fir 7" dia., bears S.15°E., 12 lks. dist. mkd. ¼ S30 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - May 15, 1969 - C.S. File 54/82-57

-----  
Found - 8" D.Fir now 18", N.18°E., 70.0 ft., shows good scar.  
7" D.Fir now 17", S.15°E., 7.9 ft., shows good scar.  
No trace of stone.

Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S  
R | S 30 R  
1 | ¼ 1  
W 1969 E

BTs tagged and OK.  
This cor. lies 223.7 ft. South of cor. for 25 & 36, T29-1W