

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 14 Page(s) 6061)

Set a basalt stone 15x12x10, 10" in ground for cor. of secs. 25 and 36, marked with 5 notches on N. and 1 notch on S. edges, from which

A Cedar 24" dia., bears S.12°W., 35 lks. dist. mkd. T29S R1W S25 BT.

A Fir 18" dia., bears N.57°W., 42 lks. dist. mkd. T29S R1W S25 BT.

Cor. Fd. and used in GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Contract #797, dated April 19, 1910 (DCSO records Vol. 15 Page(s) 6135)

Douglas Co. Surveyors Office - John M. Powell, and crew - May 15, 1969 - C.S. File 54/82-56

Found - 24" Cedar now down, S.12°W., 23.1 ft., scribe visible "S36".

18" D.Fir now 28", N.57°W., 27.7 ft. Scribe marks partly visible "B".

No trace of cor. stone.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S

R		R
1	S 25	1
W	S 36	E
	1969	

New BT - 9" R.Fir, S.82°W., 9.1 ft. scribed T29S R1W S36 CS BT.

This cor. lies 223.7 ft. North of ¼ cor. Sec. 30.