

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 14 Page(s) 6062)

Set a basalt stone 15x8x6 ins., 10" in ground for ¼ sec. cor. marked ¼ on W. face, from which

A Laurel 12" dia., bears N.21°E., 51 lks. dist. mkd. ¼ S30 BT.

A Laurel 20" dia., bears N.56°W., 6 lks. dist. mkd. ¼ S25 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Contract #797, dated April 19, 1910 - (DCSO records Vol. 15 Page(s) 6135-36)

The ¼ cor., which is a basalt stone, 5x8x6 ins. above ground firmly set, mkd. and witnessed as described by the Surveyor General. I re-establish this cor. in its original position as the ¼ sec. cor. on E. bdy. sec. 25, T29S R1W, only as follows:

Stone already set and described, from which

A Fir 36" dia., bears S.60°W., 38 lks. dist. mkd. ¼ S25 BT.

A Madrone 20" dia., bears N.56°W., 6 lks. dist. mkd. ¼ S25 BT.

I destroy marks on former bearing tree in T29S R1E.

Douglas Co. Surveyors Office - John M. Powell, and crew - May 16, 1969 - C.S. File 54/82-59

Found - Basalt stone 12"x8"x6" mkd. "¼" on West face at cor. point.

36" now 40" Fir S.60°W., 25.1 ft., alive, shows good scar.

20" now 22" Madrone N.56°W., 4.0 ft. alive, shows scar. We rescribe "¼ S25 CS BT".

Set 1" I.P. and brass cap marked: County Surveyors Office

T 29 S
¼ R S25 | R1E
1W 1969

New BT - 16" Pine S.15°W., 23.5 ft. mkd. ¼ S25 CS BT.

This corner lies on NE. slope in dense Fir, Chinquapin and Madrone.