

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 700277

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only, T29-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated Dec. 21, 1920 - (DCSO records Vol. 15 Page(s) 6138)

-----  
Set a basalt stone 20x12x8 ins., 12" in the ground for ¼ sec. cor. of sec. 19 only, marked ¼ on E. face, from which  
A Fir 7" dia., bears N.48°E., 21 lks. dist. mkd. ¼ S19 BT  
A Fir 20" dia., bears S.22°E., 15 lks. dist. mkd. ¼ S19 BT  
No iron post available for this corner.

Douglas Co. Surveyors Office - John M. Powell, and crew - May 8, 1969 - C.S. File 54/82-48

-----  
Found - 7" R.Fir now 12", N.48°E., 13.9 ft., shows good scar  
20" D.Fir now 23", S.22°E., 9.9 ft., shows good scar  
Also stone at ¼ cor. firmly set.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S  
R | R  
1 | S 19 1  
W 1969 E

BTs OK and tagged.

This cor. lies 229.0 ft. South from sec. cor. 24 & 25 only.