

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 14 Page(s) 6062)

Set a basalt stone 12x12x6 ins., 8" in ground for cor. of secs. 24 and 25, marked with 4 notches on N. and 2 notches on S. edges, from which
A Hemlock 12" dia., bears S.55°W., 6 lks. dist. mkd. T29S R1W S25 BT.
A Hemlock 18" dia., bears NW., 14 lks. dist. mkd. T29S R1W S24 BT.

Corner Used and tied in GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated Dec. 21, 1920 - (DCSO records Vol. 15 Page(s) 6138)

Douglas Co. Surveyors Office - John M. Powell, and crew - May 8, 1969 - C.S. File 54/82-49

Found - 18" R.Fir now 25" (Rec. Hemlock) N.45°W., (Rec. NW.) 9.2 ft., shows good scar.
12" Hemlock now stob, S.55°W., 4.0 ft. scribing visible T29S R1W.

Set Brass cap at cor. mkd: County Surveyors Office, 1969
T 29 S
R
1 S 24 | S19¹
S 25

Reblazed and rescribed:
25" R.Fir, N.45°W., 9.2 ft. scribed T29S R1W S24 CS BT.
New BTs- 10" D.Fir N.50½°E., 27.5 ft. scribed T29S R1W S19 CS BT.
9" R.Fir S.13°W., 12.6 ft. scribed T29S R1W S25 CS BT.
This cor. lies 229.0 ft. from ¼ S19 T29S R1E.