

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 700337

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, T29-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated Dec. 21, 1920 - (DCSO records Vol. 15 Page(s) 6138-39)

-----  
Set a basalt stone 20x10x10 ins., 15" in the ground for closing cor. of secs. 18 & 19, marked CC on E., with 3 grooves on N. and S. faces, from which  
A Cedar 20" dia., bears N.33°E., 19 lks. dist. mkd. T29S R1E S18 CC BT.  
A Hemlock 6" dia., bears S.50°E., 8 lks. dist. mkd. T29S R1E S19 CC BT.  
No iron post available for this corner.

Douglas Co. Surveyors Office - John M. Powell, and crew - May 21, 1969 - C.S. File 54/82-65

-----  
Found - 20x10x10 Corner stone in place, mkd. CC on E. side; and 2 good bearing trees.  
20" Cedar now 24", N.33°E., 12.5 ft. Show pool face.  
6" Hemlock now 8", S.50°E., (find dist. to be 18.6 ft.) (Rec. 5.8 ft.) shows good scribe of T29S 19.

Set Brass cap at cor. mkd: County Surveyors Office

	T	29	S	
R			S18	R
1	S24		S19	1
W				E
			C C	
			1969	

Rescribed 24" Cedar N.33°E., 12.5 ft. scribed T29S R1E S19 CC CS BT.

This cor. lies 211.1 ft. South of ¼ cor. S.24, T29S R1W.