

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 14 Page(s) 6063)

Set a basalt stone 12x10x8 ins., 8" in ground for ¼ sec.cor. marked ¼ on W. face, from which
A Fir 14" dia., bears S.69°E., 41 lks. dist. mkd. ¼ S19 BT
A Fir 24" dia., bears S.48°W., 34 lks. dist. mkd. ¼ S24 BT

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated Dec. 21, 1920 - (DCSO records Vol. 15 Page(s) 6139)

Intersect ¼ sec. cor. on E. bdy. of sec. 24, which is a basalt stone 4x10x8 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General. I obliterate marks on bearing tree E. of line and take new bearing tree. From the cor.
Old BT, A Fir 24" dia., bears S.48°W., 34 lks. dist. mkd. ¼ S24 BT.
New BT, A Fir 14" dia., bears N.65°W., 51 lks. dist. mkd. ¼ S24 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - May 21, 1969 - C.S. File 54/82-66

Found - No trace of corner stone.
24" Fir now 30", S.48°W., 22.4 ft. Shows good scribe of "¼ S24 BT"
14" Fir now 20", N.65°W., 33.7 ft. Shows a good face.

Set Brass cap at cor. mkd: County Surveyors Office
R T29S R
1 ¼ S24 | 1
W 1969 E
New BT - 24" Cedar S.69°W., 41.1 ft. scribed ¼ S24 CS BT.
Cor. lies 211.2 ft. N. of CC S18 & 19, T29S R1E; and 50 ft. S. of left bank of South Umpqua River.