

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 700377

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only, T29-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated Dec. 21, 1920 - (DCSO records Vol. 15 Page(s) 6139-40)

Set a basalt stone 20x10x8 ins., 15" in the ground for ¼ sec. cor. of sec. 18 only, marked ¼ on E. face, from which
A Fir 20" dia., bears N.15°E., 94 lks. dist. mkd. ¼ S18 BT
A Fir 36" dia., bears S.34°E., 120 lks. dist. mkd. ¼ S18 BT.
No iron post available for this corner.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 9, 1969 - C.S. File 54/82-75

Looked for, not found.
Second time I have looked for this corner.
I have run into cor. from the South and the North. Also, from the approx. line between 13 & 24. Orig. trees good large firs, however, I just don't find them. Good N-S blazed line. Also some E-W blazes. One area possible burn.