

TOWNSHIP 29 RANGE 01 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 14 Page(s) 6064)

Set a basalt stone 15x10x8 ins., 10" in ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Fir 12" dia., bears N.78°E., 49 lks. dist. mkd. ¼ S18 BT
A Fir 16" dia., bears S.56°W., 30 lks. dist. mkd. ¼ S13 BT

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated Dec. 21, 1920 - (DCSO records Vol. 15 Page(s) 6141)

Intersect the ¼ sec. cor., which is a basalt stone, 5x10x8 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General. I obliterate marks on bearing tree E. of line, and take new bearing tree.
From the corner.
Old BT, a Fir 16" dia., bears S.56°W., 30 lks. dist. mkd. ¼ S13 BT.
New BT, a Madrone 12" dia., bears N.48°W., 23 lks. dist. mkd. ¼ S13 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 6, 1969 - C.S. File 54/82-83

Found - D.Fir now 27", S.59°W., 20.0 ft., shows good scar.
Laurel, now 14", 15.6 ft., opened for scribe "¼".
Stone firmly set at ¼ cor. mkd. ¼ on W. face.
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S
R R
1 ¼ S13 | 1
W 1969 E
New BT - 5" Laurel N.72°W., 32.6 ft. scribed ¼ S13 CS BT.