

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 25, T29-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No 797, dated April 19, 1910 - (DCSO records Vol 25 Pg 10576)

Set a basalt stone 15x8x6", 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which

A cedar, 18" dia., bears N.29°E., 24 lks., mkd: 1/4 S30 BT.

A cedar, 15" dia., bears N.18°W., 9 lks., mkd: 1/4 S25 BT.

Fd. & used on GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10609-10)

Douglas Co. Surveyors Office - Gary Langlitz - Peter L. Earle - 10/1974 - C.S. File 57/8-10

Found - A stone 15"x8"x6" firmly set mkd. with a chiseled "+" on top and "1/4" chiseled on the west face,
From which -

An orig. 18" now 30" Incense cedar bears N.29°E., 15.8 ft. alive and well healed.

An orig. 15" now 24" Incense cedar bears N.18°W., 5.9 ft. alive and well healed.

At the corner point we set a 1"x39" IP with brass cap attached mkd.

COUNTY SURVEYOR T 29 S
OFFICE S 25 | S 30
1974 1/4

R1E R2E

We place the orig. stone alongside the brass cap.