

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Cor. Secs. 18, 19, 13 & 24 T29-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10619)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 13, 18, 19, & 24 with brass cap mkd:

T29S
R1E R2E
S 13 | S 18
S 24 | S 19
1921

from which

- A fir, 18" dia. bears N.65°E., 15 lks mkd: T29S R2E S18 BT
- A fir, 10" dia. bears S.56°E., 17 lks mkd: T29S R2E S19 BT
- A fir, 20" dia. bears S.50°W., 17 lks mkd: T29S R1E S24 BT
- A pine, 20" dia., bears N.27°W., 20 lks., mkd: T29S R1E S13 BT.

U.S. Forest Service, Tiller Ranger District -3/21/1945 (Filed Nov. 16, 1973) - C.S. File 56/40-59

-
- Found - Brass cap
18" D.F., N. 65°E., 15', tagged
20" P., N.27°W., 20'
10" D.F. S.36°E., 17'
20" D.F., S.50°W., 20'

Note - Best route to cor. use F.S. Rd. No. 291.