

TOWNSHIP 29 RANGE 02E POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 12, 13 & 18 T29-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10620)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 7, 12, 13, & 18, with brass cap mkd:

T29S
R1E R2E
S 12 | S 7
S 13 | S 18
1921

from which

- A fir, 36" dia., bears N.40°E., 35 lks mkd: T29S R2E S7 BT
- A pine, 20" dia., bears S.89°E., 56 lks., mkd: T29S R2E S18 BT.
- A fir, 40" dia. bears S.53°W., 44 lks mkd: T29S R1E S13 BT
- A madrona, 14" dia., bears N.28°W., 70 lks., mkd: T29S R1E S12 BT.

U.S. Forest Service, Tiller Ranger District -4/6/1961 (Filed Nov. 16, 1973) - C.S. File 56/40-58

Found - Brass cap
BTs same as in GLO notes

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Terrie Plouff & Teresa Buley, witnesses - Sept. 28, 1981 - C.S. File 61/27-57

Found - Orig GLO 1921 Brass Cap, firmly set, protruding 14" out of ground, properly marked.
BTs - Orig. 36" Fir, now 36" stump with well healed blaze, bears N.40°E., 23.1 ft.
Orig. 20" Pine, now 22" stump 8 ft. tall, with bark gone and no face visible, bears S.82°E., 37.0 ft. (Rec. S.89°E.)
Orig. 40" Fir, now 36" stump, bears S.53°W., 29.0 ft., with well healed blaze.
Orig. 14" Madrone, now 17", alive, with partially healed blaze with fragments of scribed "S R BT" visible, bears N.28°W., 42.9 ft. (Rec. 46.2 ft) (very steep bank).
New BTs- 3½" Fir bears N.85°W., 8.4 ft., scribed "BT" (Due to the size of tree, no other scribing was done).
Note - Corner lies in a clearcut
Rock outcropping on South side of road bears N.33°W., 100 ft.± from corner.